

### WEIGHING SCALES



#### PS-50 / PS-60

- Back-light LCD display. 5 Digits 20 mm height.
- PS-50 model: splash proof housing, simmlar IP-64.
- PS-60 model: water proof housing, simmlar IP-68.
- Programs: weight, unit conversion, auto power off function.
- Mains and internal battery.
- Capacity / display resolution:  
PS-50 model: 3 kg - 0,5 g / 6 kg - 1 g / 15 kg - 2 g (6.000 divisions).
- PS-60 model: 3 kg - 1 g / 6 kg - 2 g / 15 kg - 5 g (3.000 divisions).
- Internal resolution: 1/150.000.
- Stainless steel pan: 190 x 230 mm.

### COUNTING SCALES



#### PC-50

- 3 LCD back-light displays. 5 Digits 20 mm height.
- Programs: piece counting, preset tares, pieces checking alarm, accumulation.
- Mains and internal battery.
- Capacity / display resolution (30.000 divisions):  
3 kg - 0,1 g / 6 kg - 0,2 g / 15 kg - 0,5 g / 30 kg - 1 g.
- Internal resolution: 1/600.000.
- Stainless steel pan: 225 x 295 mm.
- RS-232: optional.

### PRECISION BALANCES



#### PB-60

- Back-light LCD display. 5 Digits 15 mm height.
- Programs: piece counting, percent weighing, accumulation, unit conversion.
- Mains and internal battery.
- Capacity / display resolution (60.000 divisions):  
300 g - 0,005 g / 600 g - 0,01 g / 1.500 g - 0,02 g / 3.000 g - 0,05 g.
- Internal resolution: 1/600.000.
- Wind shield included in 300 and 600 g models.
- Stainless steel pan:  
Ø 120 mm (up to 600 g models), 122 x 142 mm (more than 600 g models).
- RS-232: optional.

## INDICATORS



### VC-50

- Connectable to platforms up to 4 loadcells.
- ABS housing, high robustness.
- Back-light LCD display. 5 Digits 24 mm height.
- Programs: piece counting, checkweighing, accumulation, unit conversion.
- Mains and internal battery.
- Capacity / display resolution: programmable up to 15.000 divisions.
- Internal resolution: 1/600.000.
- RS-232: optional.

### VC-60S

- Connectable to platforms up to 4 loadcells.
- Stainless steel housing, with bracket for table or wall mounting.
- Red LED display. 6 Digits 20 mm height.
- Programs: piece counting, checkweighing, accumulation, unit conversion.
- Mains.
- Capacity / display resolution: programmable up to 15.000 divisions.
- Internal resolution: 1/600.000.
- RS-232: optional.

### Remote display RD-3

- High robustness metallic housing: 540x180x55 mm.
- Red LED display, 5 digits 3" (76,2 mm) height.
- Connectable to VC-50, VC-60S indicators (others, please consult).
- Maximum cable distance: 10 m.
- Mains.

## SINGLE LOADCELL PLATFORMS



### S-3545, M-4252, L-6080

- High robustness construction in steel (S-3545 and L-6080 models) or aluminium (M-4252 model).
- Stainless steel plate.
- Connectable to VC-50, VC-60S indicators (others, please consult).
- Column bracket: optional.

Model	S-3545	M-4252	L-6080
Dimensions (cm)	35 x 45	42 x 52	60 x 80
Capacity (kg)	30, 60, 150	60, 150, 300	300, 600

## INDUSTRIAL SCALES (Indicator + Platform + Column)



### SVC-50, MVC-50, LVC-50

Model	SVC-50	MVC-50	LVC-50
Indicator	VC-50	VC-50	VC-50
Platform	S-3545	M-4252	L-6080
Capacity (kg)	30, 60, 150	60, 150, 300	300, 600